



SPECIFICATION SHEET
FOR BEST-Flex Model "L"
STAINLESS STEEL CHIMNEY LINER

Phone: 888-900-8106
 Fax: 888-392-4432
 Web: www.NewEnglandChimneySupply.com
 280 Commerce Street, Williston VT 05495

BEST-Flex Model "L"
STAINLESS STEEL CHIMNEY LINER



BEST-Flex Model "L" Stainless Steel Chimney Liner is manufactured by New England Supply Inc. Located in Williston, VT.

The BEST-Flex lining system is designed and UL listed to be installed inside masonry chimneys. BEST-Flex liners are used to vent the flue gases and combustion byproducts produced by appliances that burn oil, gas, or solid fuels.

BEST-Flex Stainless Steel Chimney Liners are tested and listed by Underwriters Laboratories to UL 1777 & ULC-S635.

PRODUCT INFORMATION FOR BEST-Flex Model "L" CHIMNEY LINER

- The BEST-Flex Stainless Steel Flexible Chimney liner is designed to reline existing chimneys or to be used as a liner in new construction. Manufactured with the highest quality, mill certified alloy. BEST-Flex Stainless Steel Flexible Chimney Liner has a high acid fighting capability. Listed by UL Laboratories to UL 1777 & ULC-S635 standard for zero clearance installation. BEST-Flex can be used to vent wood, wood pellet, coal, non-condensing gas and oil, making it the choice for venting all standard efficiency installations. BEST-Flex is available in 3" to 18" diameters to cover a wide range of requirements found in the field today.
- The manufacturing systems used to make BEST-Flex utilizes a continuous strip of stainless steel, 7-ply interlocked and crimped to produce a gas and water tight lining system of superior strength and durability. BEST-Flex can be curved to go around offsets in chimneys and can be ovalized to custom sizes to fit most any installation requirement. The corrugated construction allows for expansion & contraction during the heat up & cool down periods which removes any stresses on the system.
- BEST-Flex can be insulated with either a vermiculite based poured insulation or with a foil-faced ceramic wool blanket to meet UL 1777 & ULC-S635 standards for chimney exteriors with zero clearance to combustibles.
- BEST-Flex Stainless Steel Chimney Liner comes with a Lifetime Warranty for all fuels, with appliance efficiencies at 83 percent or lower.
- Refer to installation instructions for detailed install information.

SPECIFICATION CHART	
Metal Alloy	430, 446, 316L, & 304 Stainless Steel
Thickness	.006" or .005"
Mill Certified	Yes
UL Listed	Yes 3"-12" (UL 1777 & ULC-S635)
Available Diameters	3" – 18"
Manufacturing Process	Corrugated 7-ply interlocked & crimped

